## TECHNICAL DATA SHEET

Epoxy resins yield extremely durable and attractive powder coatings due to their excellent overall chemical resistance, electrical insulation characteristics and inherent flow and mechanical properties. These powder coatings are typically applied to automotive parts, electrical equipment, office and home furniture, power and hand tools, wire goods, appliance components and related items. While epoxies provide excellent corrosion resistance, their chalking and yellowing characteristics generally make them unsuitable for use in decorative exterior applications

PRODUCT CODE:

**PRODUCT TYPE:** Epoxy

PRODUCT NAME:

| TYPICAL PROPERTIES        | TEST METHODS | RESULTS             |
|---------------------------|--------------|---------------------|
| Specific Gravity          | PCI # 4      | 1.2-1.8             |
| Coverage                  | Theoretical  | 129 Sqft/lb @ 1 mil |
| Gloss @ 60 Degree         | ASTM D523    | 0-90                |
| Over Bake Resistance      | ASTM D2454   | Good                |
| Pencil Hardness           | ASTM D3363   | H - 2H              |
| Direct Impact             | ASTM D2794   | 160 in.lbs.         |
| Reverse Impact            | ASTM D2794   | 160 in.lbs.         |
| Cross Hatch, Adhesion     | ASTM D3359B  | Pass                |
| Mandrel Bend, Flexibility | ASTM D522    | 1/4" no crack       |
| Solvent Resistance        | PCI # 8      | 50 + D/R            |
| Abrasion Resistance       | ASTM D1044   | Good                |
| Salt Spray                | ASTM B117    | 1000 Hrs            |
| Humidity                  | ASTM D2247   | 1000 Hrs            |

## APPLICATION Cure Schedule Rec. Film Thickness

Electostatic Spray: Cold 10' @ 400 Degree F 2.0 to 3.0 mil

Substrate: C.R.S.

Pretreatment: Bonderite 1000

Note: All tests performed on Bonderite 1000 (Iron Phosphate) treated panels.

## Shelf Life: 1 Year from the date of purchase, when stored under 75 degree F.

Warranty Policy: All sales are subject to the AmeriCoats Standard Terms and Conditions then in effect, a copy of which can be found at [www.americoats.com/terms]. AmeriCoats will also provide a copy of the AmeriCoats Standard Terms and Conditions upon request No additional or different terms or conditions will be binding upon AmeriCoats unless specifically agreed to in writing by an authorized representative. Please review all of the AmeriCoats Standard Terms and Conditions prior to entering any agreement with AmeriCoats. THE EXPRESS WARRANTY CONTAINED IN THE AMERICOATS STANDARD TERMS AND CONDITIONS IS EXCLUSIVE AND IN LIEU OF ALL OTHER REPRESENTATIONS AND WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE. The surface preparation and application procedures and other factors that affect performance are beyond our control. Do not use this product until the current material safety data sheet and technical data sheet have been read and fully understand. You must determine the suitability of this product for your own use and assume all risks and liabilities in connection therewith.